

The Dream Machines Features Comparison Chart

Dual Purpose Lathes Spindle/Bowl

	Swing (cm)	Centers Length (cm)	Spindle In/Out	HP	Weight (kg)	Indexing	Quill Travel (mm)	Sliding Headstock	Digital Readout	Strls. Steel Ways	Warranty	Adjustable Height	Dynamic Braking	Safety Spindle Lock	Street Pricing (USD)	Comments
EBO, Inc. Model 40-25x48	101.6	122	1.25/8	2	286	OPT.	102	N	Y	N	1.5 Electric 2-Material	N	Y	N	6999	Unique design allows conversion to spindle lathe with optional accessories.
General 26020VDR	50.8	96.5	1.25/8	2	255	N	51	N	N	N	2	N	N	N	5099	
Grizzly G0694	50.8	109.2	1.25/8	3	263	24	89	N	Y	N	1	N	Y	N	2650	Outboard floor supported tool rest included.
Laguna Pinnacle MTP105	61	132	M45/4.5	3	680	24	152	N	N	N	1	N	Y	N	9175	Optional copy and spiral attachments. Spindle adapters available.
Oneway 2036	50.8	91.4	M33/3.5	2*	363	48 96 Opt.	102	N	Y	OPT.	5	Y	Y	N	**5825	Tailstock removal option. Extensive options.
Oneway 2436	61	91.4	M33/3.5	2*	386	48 96 Opt.	102	N	Y	OPT.	5	Y	Y	N	**6153	Tailstock removal option. Extensive options.
Powermatic 3520B	50.8	88.9	1.25/8	2	286	48	114	Y	Y	N	5	Y	Y	N	3300	Optional bed and tool post extension will allow 36" turning. After market tailstock removal option.
Powermatic 4224	61	106.7	1.25/8	3	385	24	114	N	Y	N	5	Y	Y	N	4825	
Rikon Woodfast 70-500	50.8	91.4	1.25/8	2	271	24	102	N	Y	N	2	N	N	N	2800	
Robust 25	63.5	71.1	1.25/8	2	285	48	102	Y	N	STD.	7	Y	Y	Y	5995	Tailstock removal option.
Robust 16	40.6/ 81.2	101/132	1.25/8	2	218	48	89	N	N	STD.	7	Y	Y	Y	**5020	Unique bed design allows turning up to 32".
Serious SL2542	60	106.7	1.5/8	3	695	48	152	N	Y	N	2	Y	Y	Y	6975	Spindle position digital readout.
Vicmarc VL300LB	60	61	1.25/8	3	386	24	76	N	N	N	1-Electric 2-Material	N	N	N	4999	
Woodtek No. 1	50.8	50.8/ 96.5	1.5/8	3	341	48	127	N	Y	N	1	N	N	N	4489	

Bowl Lathes

EBO, Inc. Model 40	63.5	NA	1.25/8	2	281	OPT	102	N	Y	N	1.5 Electric 2-Material	N	Y	N	4799	Unique design allows conversion to spindle lathe with optional accessories.
VB36	91.4	61 or 91	Bayonet	3	313	24	152	N	N	N	2-Electric 10-Material	N	Y	Y	7999	Unique bearing design and bayonet spindle mount. Tailstock removal method standard.
Vega 2600	66	43.2	1.25/8	2	227	N	229	N	N	N	1	Y	Y	N	3095	Compact footprint.
Stubby 750	76	86.4	1.25/8	2	272	24	102	N	Y	N	2	Y	Y	N	5975	Unique bed design allows multiple placement options. Compact footprint.
Oneway 2016	50.8	40.6	M33/3.5	2*	272	24	102	N	Y	OPT.	5	Y	Y	N	**5684	
Oneway 2416	61	40.6	M33/3.5	2*	295	24	102	N	Y	OPT.	5	Y	Y	N	**5996	

*Reflects 2HP Pricing.

**Based on 2HP.

Note: Prices may or may not include shipping.